

**SECTION 12491 – HORIZONTAL LOUVER BLINDS**

**PART 1 - GENERAL**

**1.01 SUMMARY**

- A. PROVIDE WINDOW COVERINGS AT ALL INTERIOR AND EXTERIOR GLAZING WITH THE EXCEPTION OF DOOR LIGHTS.
- B. ALL WINDOW OPENINGS GREATER THAN 6'-0" WIDE SHALL BE PROVIDED WITH TWO (2) BLINDS OF EQUAL WIDTH UNLESS SPECIFICALLY NOTED OTHERWISE.
- C. BLINDS FOR HOLLOW METAL VIEW WINDOWS SHALL BE BETWEEN JAMB MOUNTED AND FILL EACH INDIVIDUAL GLAZED OPENING.

**1.02 SUBMITTALS**

- A. SUBMIT FOR APPROVAL SAMPLES, SHOP DRAWINGS, COLOR SELECTIONS AND PRODUCT DATA.

**1.03 QUALITY ASSURANCE**

- A. COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.

**PART 2 - PRODUCTS**

**2.01 MATERIALS**

- A. HORIZONTAL BLINDS, RAISING AND TILTING, WAND AND CORD OPERATION; RIVIERA LIGHTMASTER DUSTGUARD AS MANUFACTURED BY LEVELOR LORENTZEN, BALI OR APPROVED EQUAL:
  - 1. SLAT WIDTH: 1".
  - 2. SLAT THICKNESS: .0085" NOMINAL.
  - 3. SLAT MATERIAL: NON-PERFORATED ALUMINUM.
  - 4. COLOR: AS SELECTED BY ARCHITECT.

**PART 3 - EXECUTION**

**3.01 INSTALLATION**

- A. TAKE FIELD MEASUREMENTS PRIOR TO FABRICATION TO ENSURE FIT. HORIZONTAL BLINDS SHALL FILL WINDOW OPENINGS COMPLETELY BETWEEN JAMBS AND BETWEEN HEAD AND SILL.
- B. INSTALL MATERIALS AND SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS. INSTALL MATERIALS AND SYSTEMS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH UNIFORM APPEARANCE. COORDINATE WITH WORK OF OTHER SECTIONS.

**WEST NAVARRE INTERMEDIATE SCHOOL**  
**5 CLASSROOM ADDITION**

- C. RESTORE DAMAGED FINISHES AND TEST FOR PROPER OPERATION. CLEAN AND PROTECT WORK FROM DAMAGE.

END OF SECTION